

IN THE CLAIMS:

Please cancel claims 4, 5, 45 and 46 without prejudice. Please amend the following claims:

1. (Currently Amended) A submerged intake filter assembly comprising:
a cylindrical screen having a screen longitudinal axis, a first end, and a second end, the cylindrical screen defining an interior between the first end and the second end;
a primary flow modifier pipe having a diameter less than that of the cylindrical screen and a primary longitudinal axis parallel to the screen longitudinal axis, the primary flow modifier pipe extending into the interior of the cylindrical screen through the first end of the cylindrical screen, thereby forming an annular space between the primary flow modifier pipe and the cylindrical screen, wherein the primary flow modifier pipe and the cylindrical screen are eccentric at the first end; and
a secondary flow modifier pipe positioned in the annular space and extending into the interior of the cylindrical screen.
2. (Original) The submerged intake filter assembly of claim 1, wherein the secondary flow modifier pipe defines a secondary longitudinal axis that is at an angle to the primary longitudinal axis.
3. (Currently Amended) The submerged intake filter assembly of claim 2, further comprising a second secondary flow modifier pipe positioned in the annular space and extending into the interior of the cylindrical screen, the second secondary flow modifier pipe extending into the screen interior a different distance ~~from the~~ than the secondary flow modifier pipe.
4. (Canceled)
5. (Canceled)
6. (Original) The submerged intake filter assembly of claim 1, wherein the primary flow modifier pipe includes a primary inlet end and the secondary flow modifier pipe

includes a secondary inlet end and the secondary inlet end extends further into the interior of the cylindrical screen than does the primary inlet end.

7. (Original) The submerged intake filter assembly of claim 6, further comprising a second secondary flow modifier pipe positioned in the annular space and extending into the interior of the cylindrical screen, the second secondary flow modifier pipe extending into the screen interior a different distance from the secondary flow modifier pipe.

8. (Original) The submerged intake filter assembly of claim 1, wherein the primary flow modifier pipe includes a primary inlet end and the secondary flow modifier pipe includes a secondary inlet end and the primary inlet end extends further into the interior of the cylindrical screen than does the secondary inlet end.

9. (Original) The submerged intake filter assembly of claim 8, further comprising a second secondary flow modifier pipe positioned in the annular space and extending into the interior of the cylindrical screen, the second secondary flow modifier pipe extending into the screen interior a different distance from the secondary flow modifier pipe.

10. (Original) The submerged intake filter assembly of claim 1, further comprising a second secondary flow modifier pipe having a second secondary longitudinal axis positioned in the annular space and extending into the interior of the cylindrical screen.

11. (Original) The submerged intake filter assembly of claim 10, wherein the secondary flow modifier pipe defines a secondary longitudinal axis, the secondary longitudinal axis and the second secondary longitudinal axis being positioned different distances from the primary longitudinal axis.

12.-14. (Withdrawn)

15. (Currently Amended) A submerged intake filter assembly, comprising:
a cylindrical screen having a screen longitudinal axis, a first end, and a second

end, the cylindrical screen defining an interior between the first end and the second end;

a primary flow modifier pipe having a primary longitudinal axis and extending into the interior of the cylindrical screen through the first end of the cylindrical screen, the screen longitudinal axis and the primary longitudinal axis being collinear and the cylindrical screen having a greater diameter than the primary flow modifier pipe, thereby creating an annular space between the primary flow modifier pipe and the first end of the screen; and

a secondary flow modifier pipe positioned in the annular space and extending into the interior of the cylindrical screen, wherein the primary flow modifier pipe and the secondary flow modifier pipe are eccentric at the first end.

16. (Original) The submerged intake filter assembly of claim 15, wherein the primary flow modifier pipe includes a primary inlet end and the secondary flow modifier pipe includes a secondary inlet end and the secondary inlet end extends further into the interior of the cylindrical screen than does the primary inlet end.

17. (Original) The submerged intake filter assembly of claim 16, wherein the secondary flow modifier pipe includes a secondary longitudinal axis that is at an angle to the screen longitudinal axis.

18. (Original) The submerged intake filter assembly of claim 15, wherein the primary flow modifier pipe includes a primary inlet end and the secondary flow modifier pipe includes a secondary inlet end and the primary flow modifier pipe extends further into the interior of the cylindrical screen than does the secondary inlet end.

19. (Original) The submerged intake filter assembly of claim 18, wherein the secondary flow modifier pipe includes a secondary longitudinal axis that is at an angle to the screen longitudinal axis.

20. and 21. (Withdrawn)

22. (Currently Amended) A submerged intake filter assembly, comprising:

a round cylindrical screen having a first end, a second end, and an inside surface defining an interior between the first end and the second end;

a round inlet pipe having an outer surface and an open end providing a passageway from outside the inlet pipe to inside the inlet pipe, the inlet pipe extending into the interior of the cylindrical screen through the first end of the cylindrical screen to create an annular space between the outer surface of the inlet pipe and the first end of the cylindrical screen;

at least one secondary inlet pipe extending into the interior of the cylindrical screen;

an end plate coupled to the cylindrical screen at the second end of the cylindrical screen and substantially closing the annular space between the outer surface of the inlet pipe and the first end of the cylindrical screen; and

a base plate coupled to the inlet pipe and the cylindrical screen at the first end of the cylindrical screen and substantially closing the annular space between the outer surface of the inlet pipe and the first end of the cylindrical screen.

wherein the round inlet pipe defines a first longitudinal central axis and the cylindrical screen defines a second longitudinal central axis and the first longitudinal central axis is spaced apart and parallel to the second longitudinal central axis.

23. (Previously Presented) The submerged intake filter assembly of claim 22, wherein the at least one secondary inlet pipe comprises a single secondary inlet pipe positioned in the annular space and extending into the interior of the cylindrical screen through the first end of the cylindrical screen.

24. (Original) The submerged intake filter assembly of claim 23, wherein the inlet pipe extends further into the interior of the cylindrical screen than does the secondary inlet pipe.

25. (Original) The submerged intake filter assembly of claim 23, wherein the secondary inlet pipe extends into the interior of the cylindrical screen at an angle to the

first longitudinal axis.

26. (Previously Presented) The submerged intake filter assembly of claim 22, wherein the at least one secondary inlet pipe comprises a plurality of secondary inlet pipes, each positioned in the annular space and extending into the interior of the cylindrical screen through the first end of the cylindrical screen.

27. (Original) The submerged intake filter assembly of claim 26, wherein at least two of the plurality of secondary inlet pipes extend different distances into the interior of the cylindrical screen.

28. (Original) The submerged intake filter assembly of claim 26, wherein the plurality of secondary inlet pipes extend into the interior of the cylindrical screen at an angle to the first longitudinal axis.

29. - 35. (Canceled)

36. (Currently Amended) A submerged intake filter assembly comprising:
a cylindrical screen having a screen longitudinal axis, a first end and a second end, the cylindrical screen defining an interior between the first end and the second end;
a primary flow modifier pipe having a diameter less than that of the cylindrical screen and a primary longitudinal axis parallel to the screen longitudinal axis, the primary flow modifier pipe extending into the interior of the cylindrical screen through the first end of the cylindrical screen, thereby forming an annular space between the primary flow modifier pipe and the first end of the screen; [[and]]
a secondary flow modifier pipe having an interior completely positioned in the annular space and extending into the interior of the cylindrical screen; and
a second secondary flow modifier pipe having a second secondary longitudinal axis and an interior completely positioned in the annular space and extending into the interior of the cylindrical screen, wherein the secondary flow modifier pipe defines a secondary longitudinal axis, the secondary longitudinal axis and the second secondary

longitudinal axis being positioned different distances from the primary longitudinal axis.

37. (Original) The submerged intake filter assembly of claim 36, wherein the secondary flow modifier pipe defines a secondary longitudinal axis that is at an angle to the primary longitudinal axis.
38. (Original) The submerged intake filter assembly of claim 36, wherein the primary flow modifier pipe and the cylindrical screen are eccentric at the first end.
39. (Original) The submerged intake filter assembly of claim 36, wherein the primary flow modifier pipe includes a primary inlet end and the secondary flow modifier pipe includes a secondary inlet end and the secondary inlet end extends further into the interior of the cylindrical screen than does the primary inlet end.
40. (Original) The submerged intake filter assembly of claim 39, further comprising a second secondary flow modifier pipe positioned in the annular space and extending into the interior of the cylindrical screen, the second secondary flow modifier pipe extending into the screen interior a different distance from the secondary flow modifier pipe.
41. (Original) The submerged intake filter assembly of claim 36, wherein the primary flow modifier pipe includes a primary inlet end and the secondary flow modifier pipe includes a secondary inlet end and the primary inlet end extends further into the interior of the cylindrical screen than does the secondary inlet end.
42. (Original) The submerged intake filter assembly of claim 41, further comprising a second secondary flow modifier pipe positioned in the annular space and extending into the interior of the cylindrical screen, the second secondary flow modifier pipe extending into the screen interior a different distance from the secondary flow modifier pipe.
43. (Canceled)

44. (Previously Amended) The submerged intake filter assembly of claim 37, further comprising a second secondary flow modifier pipe positioned in the annular space and extending into the interior of the cylindrical screen, the second secondary flow modifier pipe extending into the screen interior a different distance from the secondary flow modifier pipe.

45. (Canceled) The submerged intake filter assembly of claim 36, further comprising a second secondary flow modifier pipe having a second secondary longitudinal axis and an interior completely positioned in the annular space and extending into the interior of the cylindrical screen.

46. (Canceled) The submerged intake filter assembly of claim 45, wherein the secondary flow modifier pipe defines a secondary longitudinal axis, the secondary longitudinal axis and the second secondary longitudinal axis being positioned different distances from the primary longitudinal axis.

Please add the following new claims:

47. (New) A submerged intake filter assembly comprising:

a cylindrical screen having a screen longitudinal axis, a first end, and a second end, the cylindrical screen defining an interior between the first end and the second end;

a primary flow modifier pipe having a diameter less than that of the cylindrical screen and a primary longitudinal axis parallel to the screen longitudinal axis, the primary flow modifier pipe extending into the interior of the cylindrical screen through the first end of the cylindrical screen, thereby forming an annular space between the primary flow modifier pipe and the cylindrical screen; and

a secondary flow modifier pipe positioned in the annular space and extending into the interior of the cylindrical screen, wherein the secondary flow modifier pipe defines a secondary longitudinal axis that is at an angle to the primary longitudinal axis.

48. (New) A submerged intake filter assembly comprising:

a cylindrical screen having a screen longitudinal axis, a first end, and a second end, the cylindrical screen defining an interior between the first end and the second end;

a primary flow modifier pipe having a diameter less than that of the cylindrical screen and a primary longitudinal axis parallel to the screen longitudinal axis, the primary flow modifier pipe extending into the interior of the cylindrical screen through the first end of the cylindrical screen, thereby forming an annular space between the primary flow modifier pipe and the cylindrical screen;

a secondary flow modifier pipe positioned in the annular space and extending into the interior of the cylindrical screen; and

a second secondary flow modifier pipe having a second secondary longitudinal axis positioned in the annular space and extending into the interior of the cylindrical screen, wherein the secondary flow modifier pipe defines a secondary longitudinal axis, the secondary longitudinal axis and the second secondary longitudinal axis being positioned at a distance from the primary longitudinal axis.